

MURALGIPS SUPER COPRENTE

TECHNICAL SHEET

GENERAL PROPERTIES

It is a high covering, transparent, vapour permeable, smooth, matt paint for interiors with a low environmental impact, that allows to obtain a pleasant finish, already with only ONE COAT of application. The product's formulation is based on micro-emulsions in water dispersion strongly anchoring and penetrating, pigments and fillers that make the product ideal for use on plaster board, civil plasters both new and old, gypsum plasters, already painted walls even if painted with dark or intense colours. MURALGIPS SUPER COPRENTE contributes to the hiding of imperfections caused by the screeding of the joints between plaster board panels, improving the aesthetic appearance of the finish. Painting is anti-drip.

INSTRUCTIONS

Substrate preparation:

Clean the surface to be painted, removing all dust, dirt and any loose or flaking material. On very absorbent or crumbly surfaces, apply the necessary primer, ECOFIX NANO-TECH diluted to 100% with water. On plaster board surfaces or surfaces in good condition, after having cleaned the surface and eliminated the main imperfections, it is possible to apply the product without the use of a sealer or primer.

APPLICATION

Apply MURALGIPS SUPER COPRENTE as follows:

- Apply one or two coats of MURALGIPS SUPER COPRENTE with a roller or brush, depending on the desired covering. Apply the product ready to use or dilute at the most 10% with water, if it is too thixotropic for brush or roller application. Wait 6 hours between one hand and the other.
- Do not apply at ambient/substrate temperature below +5°C or above +35°C.
- Wash hands etc. with soap and water after handling the product.
- Wash equipment with water.
- Store in cool premises, under frost proof conditions.
- Use products in compliance with the current Health & Safety Regulations. Do not release containers to the environment after use.
- Refer to the PSDS for further details.



Via del Tresaccio
CITTA' DELLA PIEVE (PG)
Tel. 0578 21349 r.a.
Fax 0578 20809
e-mail info@kellycolor.it



Certificato n°: 208892

TECHNICAL PROPERTIES

SPECIFIC WEIGHT: 1,51 ± 0,05 Kg./lt a 25° C (ASTM D1475-60)

VISCOSITY AT 20 °C: Tixotropic

ASPECT OF FILM: Matt

COLOUR: White and Tinting System

COVERAGE: 12 - 14 mq./lt one coat

SIZE: 4 - 14 Lt

DRYING AT 20 °C

TOUCH DRY: 3 hrs

THROUGH DRYING : 24 hrs

TENDER SPECIFICATION ITEM

MURALGIPS SUPER COPRENTE

Application on treated surfaces of one layers of a high covering, transpirant, vapour permeable, smooth, matt paint for interiors with a low environmental impact, based on micro-emulsions in water dispersion strongly anchoring and penetrating type MURALGIPS SUPER COPRENTE. All must be carried out in accordance with the norms of application, at a cost of m² inclusive of materials and labour.



Via del Tresaccio
CITTA' DELLA PIEVE (PG)
Tel. 0578 21349 r.a.
Fax 0578 20809
e-mail info@kellycolor.it

The data herein were correct at the time of Quality Control & refer to standardized environmental conditions. The same are to be considered as a guide

Revision 1 – 06/2018